2025/10/13 22:10 1/3 iWAREHOUSE - PrePaid Card API

# **iWAREHOUSE - PrePaid Card API**

Prepaid Cards Assume the following:

- Prepaid Cards can be sold from the Website or via POS.
  - On a successful sale (ie payment) the website should hit our prepaid card API and get a code returned.
  - That code should be emailed to the customer
- The Code will be
  - generated as a random non-sequential code so that people can't guess a valid code.
  - Ability to printed/scanned as a barcode and or typed into the POS.

#### **CREATE NEW CARD**

Example URL to create a new card:

http://ZZZ.iposwarehouse.com/core/sales/cards/prepaid/prepaid\_api.asp?log=AAAA&pwd=BBBB&qty=CCCC&expiresyears=DDDD&prd=EEEE&site=FFFF

#### **Returns:**

```
{
    "CardKey": 55271,
    "CardCode": "PV8BEX540B",
    "CardActive": true,
    "SiteKey": 0,
    "CustomerKey": 0,
    "ProductKey": 1836,
    "DriveCampaignKey": 0,
    "CardOpeningDteTme": "19/03/2019",
    "CardOpeningBalance": 1,
    "CardOpeningBalanceManual": 0,
    "CardBalanceDteTme": "",
    "CardBalance": 1,
    "CardExpiryDate": "19/09/2019",
    "CardNotes": ""
}
```

## **READ EXISTING BALANCE**

The API can also be used to read the balance of an existing card:

 $http://ZZZ.iposwarehouse.com/core/sales/cards/prepaid/prepaid_api.asp?log=AAAA\&pwd=BBBB\&card=PV055134$ 

```
{
    "CardKey": 55272,
    "CardCode": "PVMQ7NJ236",
```

```
"CardActive": true,
"SiteKey": 0,
"CustomerKey": 0,
"ProductKey": 1836,
"DriveCampaignKey": 0,
"CardOpeningDteTme": "19/03/2019",
"CardOpeningBalance": 1,
"CardOpeningBalanceManual": 0,
"CardBalanceDteTme": "",
"CardBalance: 1,
"CardExpiryDate: "19/09/2019",
"CardNotes": ""
```

### **NOTES**

- The API creates one gift card at a time
- The Code
- has a prefix (in this case PV) but the prefix could be anything. (Allows the POS to recognise a card using the prefix)
- is checked against the database before being returned so it us unique (not used before)
  - ∘ is always UPPER CASE
  - can be converted to a Barcode using a Barcode Font in an email or HTML page. (this is not the job of the API).
- There are many fields returned, most of which you don't need, the important fields are CardCode, CardBalance, and CardExpiryDate
- Substitute AAAA and BBBB for your login details.
- Substitute CCCC for the quantity.
- Substitute EEEE for the product key.
- Where FFFF is the site key
- We suggest using POSTMAN to prove that the API works and you can use this to troubleshoot your code.
- We suggest you log every call and response to the API so that we can compare logs if needed.
- Be aware that ISON is case sensitive

# **OPTIONAL PARAMETERS**

rego - attach the prepaid card to a REGO

#### **EXPIRY**

• Other expiry options are expiresdays=X, expiresmonths=X, expiresyears=X, expires=date

2025/10/13 22:10 3/3 iWAREHOUSE - PrePaid Card API

From:

https://wiki.imagatec.com.au/ - Imagatec Wiki

Permanent link:

https://wiki.imagatec.com.au/doku.php?id=customer\_portal:integration:cardsprepaid

Last update: 2025/07/14 14:48

